

SANVO 三和®

低碳高遮盖 净白内墙漆

- ☑ 低碳健康
- ☑ 超白靓家
- ☑ 遮盖力强



产品介绍

三和低碳高遮盖净白内墙漆延续了三和漆一贯的健康理念，精选低碳环保材料精制而成。是一款净味环保、固含量高、遮盖力好、涂刷面积大、施工性能优良、性价比高的内墙装饰涂料。

Sanvo Low-Carbon Full-Hiding Pure White Interior Paint has kept SANVO paint's consistent healthy philosophy. It's formulated from selected low-carbon environmental raw materials, and is an odourless, environmental, high solid, strong covering, low consumption and cost effective interior decoration paint with excellent performances.

主要成分

丙烯酸共聚物、乳液、颜填料、助剂和水。
styrene-acrylate copolymers, pigments and fillers, agents, water

理论耗漆量

8~10m²/kg/层(以30um厚干漆膜计)，施工方法、施工环境及涂刷表面情况等因素，会影响实际的消耗量。

8~10m²/kg/layer (calculated by 30um dry paint). Application, environment and substrate will affect actual consumption.

注意事项

1. 施工前将待涂墙面清理干净。保证无油脂、霉、藻等其他附着物，水泥面应待其干透后(含水率低于10%，pH值低于10)再施工；
 2. 使用时必须搅均匀；
 3. 温度8℃以下，相对湿度高于85%时，不宜使用。
 4. 施工时必须注意空气流通，喷涂时，应佩戴口罩，如沾染皮肤及衣物，请在润湿时用水清洗。
1. Clean the wall before application to avoid oil, grease, mould and algae etc. New plaster, sand or cement surfaces should be properly prepared and let thoroughly dry (water content below 10%, pH below 10) before applying this product.
 2. Stir thoroughly before using.
 3. Do not apply when temperature is below 8℃ or relative humidity is above 85%
 4. Keep the application area well ventilated. Wear protective masks. If skin or clothing are stained by this product, soak and wash with water.

施工方法

刷涂、滚涂、高压空气喷涂或高压无气喷涂。
brush painting, roll painting, high pressure air spray, or high pressure airless spray



刷涂



滚涂



喷涂

SANVO 三和® 美国三和化工科技集团监制
SINCE 1997
制造商：广东三和化工科技有限公司
地址：中山黄圃大岑工业区
http://www.sanvo.us
客服热线：400-103-0301